


PRODUCT
Colours100
PEARL

Vinyl Plank

180
HEATHER

Vinyl Plank

300
TOPAZ

Vinyl Plank

350
TOTARA

Vinyl Plank

500
ROSE GOLD

Vinyl Plank

520
TOI TOI

Vinyl Plank

550
TUSOCK

Vinyl Plank

580
SUMMIT

Vinyl Plank

700
LIMESTONE

Vinyl Plank

720
TITANIUM

Vinyl Plank

750
PAUA

Vinyl Plank

780
ONYX

Vinyl Plank

AQUILA  VINYL PLANK

Aquila is a stunning vinyl plank range that features extra wide planks in a modern Nordic inspired colour palette. Durable, easy to maintain and water resistant[^] Aquila is the perfect choice to bring style to all areas of your home, including wet areas.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. [^]Subject to proper installation and maintenance.

PRODUCT

Specifications

AQUILA Direct Stick Plus - Vinyl Plank Product Details

Technical Data		Technical Data	
Type	Vinyl Plank	Colours	12
Plank Thickness	4.5mm	Protective Coating	Superguard®
Wear Layer	0.55mm	Finish	Matte
Dimensions	1498mm (L) x 246mm (W)	Surface	Embossed
Planks per Box	6	Profile	Micro Bevel
M ² per Box	2.21m ²	M ² per Pallet	119.34m ²
Installation Method	Direct Stick  Please refer Installation instructions for further details		

Performance

Classification	23, 33				ISO 10582	
Dimensional Stability	Length: 0.05% Width: 0.05% Curling: 0.00%				ISO 23999	
Abrasion Rating	Group T				EN 660-2	
Residual Indentation	<0.1mm				ISO 24343-1	
Castor Chair	No Damage				ISO 4918	
Impact Sound Reduction	Ln,W 58 IIC 51 Product tested over Damtec 2.0mm Colour Underlay				ISO 10140-3 ASTM E492-09	
Light Fastness	≥ 6				EN ISO 105-B02	
Light Reflectiveness Values	100 Pearl	62.11%	180 Heather	17.5%	300 Topaz	27.63%
	350 Totara	22.19%	500 Rose Gold	49.53%	520 Toi Toi	34.77%
	550 Tussock	28.25%	580 Summit	30.14%	700 Limestone	21.89%
	720 Titanium	36.48%	750 Paua	20.7%	780 Onyx	26.58%
Slip Resistance	P3, R9				AS/NZ 4586	
Residential Warranty*	25 Years					
Commercial Warranty†	15 Years					
Reaction to Fire	CRF 8.6 kW/m² Smoke Value 217%.min				EN ISO 9239	
Suitable for wet areas	Yes - subject to proper installation and maintenance					
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide www.godfreyhirst.com					

Sustainability

VOC Rating	Passes CETEC VOC test
Accreditation	Manufactured under a management system certified as complying with ISO 9001 & ISO14001

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.

Test results and certificates are available on request.

